



Product page

BATTERY CHARGER DIGITAL GDB 24V / 12V-200 Item No.: 85128

Simply connect the charger, select charging mode and the intelligent charging technology does the rest

- for all common **12 V and 24 V battery types**
- direct charging of a battery connected in the vehicle
- battery **-friendly 10-stage charging process**
- types of batteries: **PB, GEL, AGM**
- fully automatic microprocessor-controlled diagnostic, rescue, loading and maintenance function
- constant charge maintenance
- overcharge, short circuit, overheating, reverse polarity protection
- spark and electronics safe
- jump start function **up to 200 A**
- rescue function, especially for deeply discharged batteries (from 1.5V)
- LED display (volt charging current and charging progress)
- mobile

PB - lead-acid battery

GEL - gel battery

AGM - flow battery (start-stop autom.)

MF - maintenance-free battery

WET - wet battery

Technical information:

Rated voltage:	230 V
Frequency:	50 Hz
Output voltage:	12 / 24 V
Fuse rating,:	16 A
Rated power:	6000 W
Effective charging current:	5/15/30/40 A
Battery capacity:	20-450 Ah
Anzahl Schmelzsicherungen:	10 Stk.
Fuse:	50 A
Starting assistance 1.5 V:	200 A
Battery start without pre-charge:	35 - 50 Ah
Battery Start with pre-charge:	65 - 100 Ah
Size LxBxH:	297 x 295 x 670 mm
Net. weight:	16,8 kg
Gross weight:	18,4 kg



VE 16



L 355 x B 315 x H 655 mm

GTIN-Code

4015671966445